

Pearl®

Ticket Issuing System

Data Sheet 001 Issue 1 05l08



Neil Briscoe Managing Director Shere

66 After the decision to integrate Oyster® capability in March 2007, Shere had the first successful trial of the product within six months and less than one year later had 59 units operational in the field. Our engineers had regular interaction with the Cubic support services which was key to ensuring a seamless integration in minimal time. ??

Pearl® at-a-glance:

- Cubic TriReader® Technology for ISO 14443 Type A and B and Cubic GO Card®
- Oyster® Retail Capability* with simplified back office messaging for ease of integration
- Can be customised to support transparent mode, enabling integration with legacy and third party applications (e.g. ITSO, 'Verband Deutscher Verkehrsunternehmen' VDV)
- Simple application programming interface
- Host library supplied for windows/x86 host platforms
- 2 Secure Access Module (SAM) slots
- For other applications please consult Cubic
- * Note: Participation in the Oyster® scheme is subject to agreement with Transport for London (TfL) and TranSys

Pearl[®] is a modular device which provides Contactless Smartcard capability for retail outlets processing Oyster[®] "products", alongside other items of sale.

By incorporating software processing capabilities, Pearl® enables integration into a range of different host devices, such as Cubic's x-PERT® retail terminal.

In turn, host equipment manufacturers can add Contactless ticketing to existing supplied equipment, or incorporate the technology into new equipment before delivery. This allows transport operators and agencies to update their existing infrastructure, using this module as the interface between Contactless Smartcards and their current equipment. The Pearl® enables participation in any required Contactless Smartcard scheme e.g. Oyster®, Integrated Transport Smartcard Organisation (ITSO) or any other scheme; assuming appropriate agreements have been reached between all relevant parties.

How it works

Pearl® is the active component between the Smartcard reader and the host system. It enables Oyster® "products" such as stored value travel or ticketing to be sold or checked in addition to enabling third party functions:-

- Adding Pearl® to a ticket-vending machine or a counter-based ticket office with a suitable host system server will enable Smartcard retailing to be integrated into existing systems.
- With the addition of a simple off-the-shelf POS (Point of Sale) terminal such as a Verifone dial up module (see Cubic datasheet Compact POS terminal 3000), Smartcard sales can be implemented into retail outlets.

Cubic has incorporated biometric technology into its systems – Cubic GO CARD® – which has Contactless Smartcard capabilities. In conjunction with Cubic Tri-Reader®, which reads and writes ISO 14443 Type A & B cards, Cubic GO CARD offers an truly flexible, open system and highly secure approach to monitoring and controlling border and transportation access.

Pearl®

Ticket Issuing System

Data Sheet 001 Issue 1 05l08

Specifications:

Modern Design

The module incorporates the smartcard reader with a processor PCB so that an efficient interchange between card and host is affected. This combines the functionality previously carried out by a separate large processor card.

Features

2 SAM slots ITSO/Oyster® Capability

Temperature & Humidity Range

Operating:

-20°C to +60°C 20 to 90% Relative Humidity

Storage:

-30°C to +75°C 10 to 90% Relative Humidity

(non-condensing).

Shock & Vibration

Shock: MIL810D, 20.0g, 11mS

Vibration: MIL810D, Method 514.3, category 8: 2.0g

Electromagnetic & Safety

EMC Directive 89/336/EEC LVD Directive 73/23/EEC

by application of the standards:

CISPR 61000-6-3, 1996-12 (formerly EN 50081-1)

Electromagnetic Compatibility-Generic Emission Standard,

Part 1: Residential, Commercial and Light Industry. IEC 61000-6-2, 1999-01 (formerly EN 50081-2)

Electromagnetic Compatibility-Generic Immunity Standard,

Part 2: Industrial Environment. EN 50121-4 Railway

Applications-Electromagnetic Compatibility, Part 4: Emission and Immunity of the Signalling and Telecommunications

Apparatus.

The Pearl® also meets: ETSI 300 330 Telecommunications Standard, Radio Equipment Operating in the Range of 9 kHz to 25 MHz.

BS EN60950-1: 2002

Information Technology Equipment - Safety

Interface Connections

Input voltage 5 to 24V dc


Power Requirement: 5 Watts minimum PSU requirement

Operating power: 0.7 Watts

Pearl® External Connections – 4RJ45 for DC power, RS 232

and a separate DC socket

Pearl® System Interfaces



Cubic Transportation Systems Ltd

European Headquarters

AFC House Honeycrock Lane Salfords Redhill Surrey

RH1 5LA

Telephone: +44 (0) 1737 782200 Fax: +44 (0) 1737 789759

